

SKU: DC-FPBC-6A-BK-ETL

CAT6A FTP CMP

LAN CABLE TEST TO 750MHz
Part No.: LX6AF11P-ETL ETL
FILE No.: 5011596 Version No.:
03 (2020.08.20)



Packaging available

- 1000ft reel

Jacket colours



CONSTRUCTION

CONDUCTOR

Material:

Solid Bare Copper

Size:

23AWG 0.022"(0.57±0.006mm)

INSULATION

Material:

SAME® FEP

OD:

0.0394"(1.00±0.05mm)

Color Code of four pairs:

Brown * White / Brown

Blue * White / Blue

Orange * White / Orange

Green * White / Green

TAPE:

PET(20/0.025mm)

DRAIN WIRE:

24AWG Solid Tinned Copper

SHIELD"

Aluminum / Poly Tape

100% coverage with 25% overlapping

RIPCORD

Kevlar

SEPARATOR

SAMP® LSZH CROSSWEB

**RoHS**

Issue Date: October '11

Revision: 4

JACKET

Material:	CMP-PVC
Nominal Thickness:	0.0197" (0.50mm)
OD:	0.291"±0.012"(7.4±0.3mm)

MARKINGS

TBD

ELECTRICAL & PHYSICAL PROPERTIES

Temperature Rating:	-20°C ~ +80°C
Voltage:	30V
Capacitance:	5.6nF/100m.Nom
Characteristic Impedance:	1-100MHz, 100±15%; 101-250Mhz, 100±22%; 250-500MHz, 100±25%
Velocity of propagation:	≥67%
DCR: Conductor:	9.38 Ohms/100m.Nom
D.C Resistance Unbalance:	≤5%

**RoHS**

Issue Date: October '11

Revision: 4

SKU: DC-FPBC-6A-BK-ETL

FREQ MHZ Max	ATT (dB/100m)	NEXT (dB)	ACRF (dB)	PS- NEXT (dB/)	PS. ACRF (dB/)	RL (dB/)	DELAY (ns/100m)	SKEW (ns/100m)
1	2.1	74.3	67.8	72.3	64.8	20.0	570	45
4	3.8	65.3	55.8	63.3	52.8	23.0	552	
8	5.3	60.8	49.7	58.8	46.7	24.5	547	
10	5.9	59.3	47.8	57.3	44.8	25.0	545	
16	7.5	56.2	43.7	54.2	40.7	25.0	543	
20	8.4	54.8	41.8	52.8	38.8	25.0	542	
25	9.4	53.3	39.8	51.3	36.8	24.3	541	
31.25	10.5	51.9	37.9	49.9	34.9	23.6	540	
62.50	15.0	47.4	31.9	45.4	28.9	21.5	539	
100	19.1	44.3	27.8	42.3	24.8	20.1	538	
200	27.6	39.8	21.8	37.8	18.8	18.0	537	
250	31.1	38.3	19.8	36.3	16.8	17.3	536	
300	34.3	37.1	18.3	35.1	15.3	16.8	536	
400	40.1	35.3	15.8	33.3	12.8	15.9	536	
500	45.3	33.8	13.8	31.8	10.8	15.2	536	


RoHS

Issue Date: October '11

Revision: 4